

**TAME IT WITH** ONE FINGER

Easy-touch setting with 6 different profiles for individual groups



manual selection

SANREMO

#### Each coffee has its own feature

this is the perfect way to bring it up



Maximum precision and full control on the three phases of coffee extraction



**POWER DRY STEAM** 

Silky milk at high capacity



GEAR PUMP PERFORMANCE

High and constant pressure in all conditions





## EVERYTHING UNDER CONTROL

System digital display to provide visibility of all working parameters



#### HEART **OF STEEL**

For maximum thermal stability:

- Groups in AISI 316 weight 22 lb / 10 kg each
- Portafilters AISI 316
- Boilers AISI 316



#### **EASY APP** Tablet barista's App

for setting parameters

**OPERA IST WITH** ACAIA DUAL SCALES Embedded ACAIA dual scales system for a perfect

coffee result in cup



Opera. The Revolution. Link to the website.

#### Characteristics



AISI 316 STEEL GROUPS WITH 22 lb / 10 kg PURE STEEL Exclusive Sanremo design ensure exceptional thermal stability and maximum resistance to oxidation and lime scale.



AISI 316 **Stainless Steel** PORTAFILTER WITH "COMPETITION FILTER"\* Exclusive Sanremo design, with shape and volume designed to capture the best coffee aromas and fragrances.



AISI 316 STAINLESS STEEL FREE MOTION STEAM TAPS Flexible control system for producing



AISI 316 STAINLESS STEEL STEAM WAND "COOL TOUCH" Anti-burning feature even in conditions of prolonged use, fitted with "Latte Art



**DELIVERY SYSTEM** (CDS)

Three phases extraction parameters full control (pre-infusion, infusion,



INDEPENDENT ADJUSTMENT OF THE PID INFUSION WATER TEMPERATURE

Precision setting (gradient ± 0.1 °C with measured constancy lower than 0.2°C).



INFUSION WATER DISPLAY dicates tea and herbal teas water brewing temperature.
(In the two group Opera it is shown with the steam boiler display)



STEAM BOILER DISPLAY

In that Boiler temperature and pressure.
(In the two group Opera it is shown with the infusion water display)



**COFFEE UNIT SINGLE DISPLAY** Controls of all coffee extraction



**MACHINE'S PROGRAMMING** PARAMETERS DISPLAY
The internal display is a handy
programming interface for the
maintenance technician.



FOR TEA AND HERBAL TEAS Instantaneous mixing of fresh water and steam for a better chemical



**EASY SERVICE** Fast access to the internal parts for quick and easy technical service.

**GEAR PUMPS** 

Dedicated to each individual group, allow to change the pressure during infusion.

STEAM CONTROL ADJUSTABLE ELECTRONIC PRESSURE SWITCH

Sensor with 0.02 bar precision that allows the chosen pressure and steam in the boiler to be kept constant in all conditions of use.

PROGRAMMABLE CUP WARMER TEMPERATURE Allows the cups to be kept at the

optimum temperature in the most different climatic conditions.



AUTO-DIAGNOSIS, STATISTICAL DATA, SCHEDULED MAINTENANÇE

MAINTENANCE
Maintenance can be scheduled according
to litres or number of coffees dispensed.



AUTO-ON, AUTO-OFF AND DAY-OFF FUNCTION Programmable on-off timer for each day and/or daily timetables.



**AUTOMATIC** CLEANING CYCLE Process for coffee



**ENERGY SAVING SYSTEM** Insulation and smart energy management to save up to 30% of energy.



**GROUP FLUSHING** With a simple pressure of the button a small quantity of water is dispensed to allow the group to be always clean.





**OPERA IST** WITH ACAIA **DUAL SCALES** 



YINOX

HIGH POWER STEAMER TERMINALS (bigger holes diameter)

STAINLESS STEEL NAKED PORTAFILTERS







VOLUMETRIC **PUMP** 

**TALL VERSION** 


# Opera 2.0

#### Versions





40.9 inches / 1040 mm



29.3 inches / 745 mm

- 2 group OP 2 steam taps
- 1 water tap
- 1 one-cup portafilters
  2 two-cup portafilters

3 group OP


- 2 steam taps 1 water tap
- 1 one-cup portafilters 3 two-cup portafilters




(€

_Technical data		2 group	3 group
voltage	٧	220 / 240 1N / 380 / 415 3N	
power input	kW	7.7	8.75
steam boiler capacity	US gal / It	2.11 / 8	2.64 / 10
services boiler resistance power	kW	3.8	3.8
external pump power	kW	0.15	0.15
preheating boiler capacity	US gal / It	0.74 / 2.8	0.74 / 2.8
preheating boiler resistance power	kW	1.6	1.6
cup-heater power	kW	0.2	0.25
units boiler capacity	US gal / It	0.264 / 1.0	0.396 / 1.5
units boiler resistance power	kW	1.6	2.4
net weight	lb / kg	200 / 91	249 / 113
gross weight (with shipping crate)	lb / kg	304 / 138	373 / 169.5

#### **OPERA TALL VERSION**



High accuracy thermal stability thanks to the Sanremo multiboiler system with sophisticated electronic boards that continuously control temperature throughout all phases of extraction. Steam and coffee circuits work totally independent to maximize performance in overse working condition (also under in every working condition (also under high workload).







#### . Opera a dream without boundaries









23-01-2013

OPERA TRAM

THANKS to EVERYROBY IT WAS A PROPRESE

MO AMERINE DAY!










thanks.









Opera started from a dream, which is both innovative and simple. An international group of coffee experts reunited together with the vision of creating the finest espresso machine ever built.

The real users of coffee machines expressed their needs without any geographical or language barriers: having a precise tool which could allow them to control and manage different parameters and extraction phases in order to best evaluate each single or specific single origin coffee blend.

Sanremo has organized a superior team starting from the initial brainstorming until the finish line, the Opera... this is a story about us, our experience, determination and passion.

Opera was born by a dream without boundaries.

Now the Opera has become a reality for the world to experience.



Opera. The full story
Watch the video.





#### Standard models

wide choice of version





Opera Black
Standard back panel: |BP5|





Opera White Standard back panel: |BP2|



Opera Steel Standard back panel: |BP1|

Opera was created to surprise in all its details: technological excellence is perfectly combined with the lines of its unique design, making it stand out and become a style icon. It also ensures ergonomics and user-friendliness in each operation for baristas, making it unparalleled among those of its kind.



#### **BP1** Etched crystal / backlight













#### Blackboard graphite rewritable



**BP5** Black / backlight







#### \_ Choose the panel

to suit your style



Back panel of each version can be customized, with finishes that meet all your needs and vision.

For example, from the blackboard to write promotions and offers for the customers, to the natural wood, to crystal or oxidized steel which give the possibility to engrave, carve or screen print a logo or a pattern...

# Opera Octane Standard back panel: |BP6| Intense, enveloping, defined: teal is a dye with a strong, bold, and elegant character, which perfectly matches Opera dark lines and flawless performances:

Tailor made finishes collection 2018



Opera Oxid
Standard back panel: |BP3|

Pure steel manually oxidised in its external parts, to further sign the tailoring of each Opera with a unique and inimitable aesthetic touch: for those who love to own original collector's items.







for those who love trends that

rhyme with sophistication.







## Control Delivery System

to act on all the extraction phases


Extraction examples of different coffee types:

BLEND / A BLEND / B SINGLE ORIGIN / C Every single origin or coffee blend has its own organic characteristics that are best expressed using different infusion styles.


By manipulating different variables and concentrations the barista can fine tune each extraction to suit their specific origin, density and roast style.

All this guarantees allows the barista to manage the amount of high pressure each coffee bean is exposed which not only preserves all of their aromas but also enhances their best features.

 $(\sim 40~{
m g})$ 



The CDS (Control Delivery System), gives the barista precise control of extraction in three phases: pre-infusion, infusion and post-infusion, considering the density and roasting of the bean.




## Pre-infusion with soft pressure

The different physical characteristics of each coffee bean, was well as its degrees of roasting and grinding, all affect the extraction process. To obtain a perfect and homogeneous extraction it is essential to control the parameters of the pre-infusion.

wet 0/10 sec

The pre-infusion is the first phase of the coffee extraction: its function is to get the powder wet and prepare it with a soft pressure (max 3 bar) for the following and optimal extraction. The pre-infusion also allows the coffee grinds to gently expand before the infusion stage which reduces the chance of channelling.



### Infusion at the maximum thermal



Thanks to the highest quality components, precision sensors (5 control points) and the Multiboiler System, Opera ensures the maximum thermal stability. adjustable to the tenth of a degree °C.

The **Tempcontrol** system allows to separately modify the water temperature for dispensing and the temperature of each group very quickly.


The outstanding performance of the Pressure Drive system, a gear pump for each group, allows an independent regulation of the ideal pressure during the infusion.

All this guarantees the perfect switch point to the coffee laver, which is the correct duration of exposure to the high pressure, preserving all the aromas, enhancing their best features.

#### Post-infusion, to collect until the last note

Depending on the type of coffee used, the regulation of a post-infusion, which may be long or short, can improve the result in the cup and eliminate the bitter notes, which may compromise the quality of the extraction.






Opera allows the adjustment of the parameters of this delicate phase, defining then the final dose dispensed in the cup (in ml or g).

The post-infusion allows to accomplish the coffee infusion in the final phase of the extraction at a lower pressure, continuing to extract soluble substances and aromas without increasing the bitter notes caused by the high pressure overextraction that normally occurs in this phase.

#### Everything under control

group display for coffee brewing





#### boiler display and hot water supply


Just a quick review: highly precise electronic sensors detect pressure, temperature, and water level. These measurements are constantly monitored in real time and accessible in a fast and secure way.

**2 GROUP DISPLAY** 









PRE-INFUSION



**INFUSION** 



**3 GROUP DISPLAY** 

#### hight performance steam function

Opera guarantees high performance and dry steam thanks to the electronic control system through an advanced transductor.



Use the best Sanremo technology, with impeccable performance, to give free rein to your creativity:

- dedicated steam boiler (high capacity and fast recovery)
- free motion steam taps
- cool-touch steam wand





Through the group display the barista can keep control of all the phases and extraction parameters according to the set profiles for that particular group:


- water temperature precise and constant throughout the extraction step
- pressure diversified for the 3 phases: pre-infusion/infusion/post-infusion
- delivered dose (ml) \*
- extraction time
- ${}^{\star}$  in the scales version it is even possible to control the espresso's weight in cup

For each group it is possible to set 6 different flavor profiles utilizing the push/pull lever in conjunction with the 3 selections of buttons.



**POST-INFUSION** 






6 profiles + 6 profiles + 6 profiles

#### Everything in an App

app dedicated to parameter settings for tablet



With the interface "Express yourself", the barista has total control of the extraction phase of his coffee and can manage each dispensing parameter according to his experience and professionalism.

To configure and set all the parameters of the machine, aspecific App has been designed, which runs on smartphone, tablet, pc...

The application "Express yourself" utilizes a graphic interface, it is both user friendly and intuitive. This interface allows the user to set each groups relative parameters accurately for the perfect extraction.

Upon choosing the group (step A) and assigned a configured profile (step B,C) will define the general parameters of extraction: temperature and doses (step D,E). At the end it is possible to adjust the parameters relative of the 3 extraction's phases: pre-infusion, main infusion, post-infusion (step F).

For each group it is possible to set:

#### Temperature


- water temperature T2
- group temperature T3
- steam temperature **T5** (unique boiler for all groups)

#### Dose


- weight of ground coffee
- water dose
- pump pressure
- coffee weight

#### Infusion


- timina
- pump pressure
- amount of water













(step **F**)

#### Adjust the 3 extractions phases

This operation is simplified by the App. Everytime the user modify one of these parameter the software update automatically. What was set prior to the modification.



STANDARD
STRONG
BALANCED
SWEET & LIGHT
<b>N</b> (set by the user)
<b>N</b> (set by the user)

CONFIGURATIONS


It is possible to save and recall new configurations set by the user or the default ones, specifically designed to allow even the less experienced bartenders to obtain immediately excellent results in the cup.

Clicking in "save new configuration" you can save your perfect espresso dispensing menu and transfer it through the Bluetooth connection into another machine.


### Opera wi-fi the easiest way

Since today on the new Opera 2.0 is easier to handle, thanks to the Sanremo Cloud and Webapp Expressyourself interface, for an even easier and interactive using experience.






- Handling through Sanremo app, from smartphone, tablet, or pc, of all configuration parameters of the machine, without the need for physically being in front of it.
- Possibility of connecting multiple machines simultaneously for sharing, modifying, and setting of recipes and configurations.
- Simultaneous monitoring and handling of multiple machines by the same owner (e.g.: franchising in different locations).
- Statistical analysis of consumption, distribution, maintenance, configuration for all connected machines.
- Remote maintenance by the technician for updating, verification of the correct settings and parameters control.



#### **INTRANET** (LOCAL WI-FI NETWORK)




#### PLUS + (USING THE LOCAL WI-FI NETWORK)

- \_ Reading and changing machine settings and parameters
- \_ Consumptions analysis for a better stock management
- \_ Meters reading of the coffee dispensed
- \_ Saving, restoring and sharing of settings (recipes) on your machines

Data exchange can only be effective in the wi-fi range.

#### INTERNET (GLOBAL NETWORK) / SANREMO CLOUD



#### PLUS + (ENABLING THE MANUFACTURER)

- Sending of App updates to the machines
- Sending new settings (recipes)
- Clearer and faster data collection aimed to resolve any technical/constructive problems Useful information for the improvement
- and evolution of the product Direct and continuous contact
- with the manufacturer

- Reading and changing of the machine settings
  - Display of historical usage data
    - Consumptions analysis for a better stock management
    - Meters reading of the coffee dispensed
    - Saving, restoring and sharing of settings (recipes) on your machines

#### PLUS + (ENABLING THE SERVICE)

- Immediate report of anomalies
- Diagnosis and possible remote troubleshooting
- Reduction of machine downtime
- Logisitic planning and organization of maintenance interventions

Developed in cooperation with

\_Innovative Scale Technology 100% accuracy



#### **Brew Ration Control**

the way to a correct extraction

In order to get a perfect result in the cup it is absolutely necessary to use the right amount of water as a function of grams of ground coffee that we have in the portafilter.


Generally for the modern espresso is extracted from 18-21 g of ground coffee, but how much product do we need to extraction in the cup for that perfect espresso?



**BREW** 

**RATIO** 


50%



**OPERA IST** WITH

**SCALES SYSTEM** 

The volumetric measurement method not ideal to test a correct extraction, because the crema influence a lot the volume of espresso.



Only the control of the **Brew Ratio** is achieved through the measurement of the weight of coffee in the filter and the weight of the dispensed product.

To achieve our target we have equipped Opera IST (Innovative Scale Technology) with scales that allow the barista to control the amount of product in the cup and reach the desired Brew Ratio.

Thanks to Opera's sophisticated technology with scales it is possible to ensure the perfect measurement of the desired Brew Ratio and obtain a perfect result in the cup.

## Innovative Scale Technology

lets you make utterly perfect coffee each and every time

The Opera IST system is a Sanremo project developed in cooperation with **Acaia**.

This system is at the forefront of technology and production quality. It lets you make utterly perfect coffee each and every time thanks to the **Brew Ratio Control**.

The barista can now operate with the machine not only through dosing the amount of water, but also visualizing the weight of the coffee in cup.

This way it is possible to "customize" every single brew as wished.



**"Dual" scale** for Sanremo Opera IST profit by Acaia Weighing Technology:

- Real-time weighing result feed back to each group head
- Noise filtering
- Zero tracking
- 1 Million internal resolution counts
- USB Rechargeable Battery

- Calibration
- Accuracy Readings from 0.1g / 0.01g
- Error Margin ± 0.05g (0.5%) A rusty traditional mechanical scale has an error range of: ±1g (10%)



For more information about our coffee machines please contact us at export@sanremomachines.com











SANREMO coffee machines s.r.l. Via Giacomo Bortolan 52 31050 Vascon di Carbonera [TV] — ITALY T +39 0422 448900 F +39 0422 448935 www.sanremomachines.com